

# Hose-End Products for Irrigation and Outdoor Watering Product Catalog



Yard Hydrants Page 16



Model B67 Page 7



Model 68 Page 7



Model 19 Page 3

**RESIDENTIAL WALL FAUCETS .....** 2-5

**RESIDENTIAL WALL FAUCETS .....** 5-6  
Automatic draining

**COMMERCIAL WALL HYDRANTS.....** 7-9

**ROOF HYDRANTS .....** 10-11

**MILD CLIMATE WALL FAUCETS ...** 12-15

**YARD HYDRANTS .....** 16  
**UTILITY HYDRANTS .....** 17

**SANITARY YARD HYDRANTS .....** 18

**VACUUM BREAKERS .....** 19

**REPAIR KITS .....** 19-24

**OBSOLETE/INDIVIDUAL PARTS...** 25-26

**TERMS & CONDITIONS .....** 27

**Residential Wall Faucets:**

|   |   |
|---|---|
| Inlet Descriptions & Rough-In Dimensions .....  | 2 |
| Model 14, 17, 16, 19, 22, V22 .....             | 3 |
| Mounting Sleeve, Stem Lock .....                |   |
| Over Sized Flange, Drywall Mounting Plate ..... |   |
| Adjustable Operating Rod .....                  | 4 |
| Model 32 Lawn Sprinkler Supply .....            | 5 |

**Residential Wall Faucets-Automatic Draining:**

|   |   |
|---|---|
| Inlets, Model 25, 27 .....  | 5 |
| Model 30, WF-30MS Mounting Sleeve, MB30BX Modular Box System, RK-30MBDR Doors, RK-Bracket ..... | 6 |

**Commercial Wall Hydrants:**

|  |   |
|--|---|
| Model 65, 67 .....   |   |
| B65/B67 Rectangular Brass Box .....                                  |   |
| RB65/RB67 Round Brass Box, MB65/MB67 Modular Box .....               |   |
| 68 Undercover Wall Hydrant™ .....                                    | 7 |
| Hot & Cold: HC67, HCB67, C22, B22, SL-65 Stem Lock, 70, Inlets ..... | 8 |
| Rough-In Dimensions .....  | 9 |

**Commercial Roof Hydrants:**

|   |    |
|---|----|
| RHY1-MS & RHY2-MS .....                         |    |
| RHMC-MS (Mild Climate), SRH-MS (Sanitary) ..... | 10 |
| Package part Numbers, Rough-In Dimensions ..... | 11 |

**Mild Climate Series:**

|  |    |
|--|----|
| 101, 122, V122, 30CC, MB221, 224, 226 .....      |    |
| C22CC, B22CC .....                               | 12 |
| 21, 24, 26, B24, B26, SL-24 Stem Lock .....      |    |
| MB24 Modular Box, B24-B26 .....                  | 13 |
| 74, 75, 76, 79, 84, 86, B74-B79, RB74-RB79 ..... |    |
| CC Rough-In Dimensions .....                     | 14 |
| 40 Series, MC Rough-In Dimensions .....          | 15 |

**Yard Hydrants:**

|  |    |
|--|----|
| Y34, Y1, Y2, R34, W34, X34, Y30, Y95 ..... | 16 |
|--|----|

**Utility Yard Hydrants:**

|   |    |
|---|----|
| Utility Hydrants & Inlets & Rough-In Dims ..... | 17 |
|---|----|


**Sanitary Yard Hydrants:**

|  |    |
|--|----|
| S3, S4, Thermaline, H34 .....              | 18 |
| Vacuum Breakers, Backflow Preventers ..... | 19 |


**Packaged Repair Kits**

|                                  |    |
|----------------------------------|----|
| Obsolete Parts .....             | 25 |
| Individual Parts .....           | 26 |
| Terms & Conditions Of Sale ..... | 27 |
| Sales Representatives .....      | 28 |


**Rough-In Dimensions / O.A.L.**



**Model  
14, 16, 17, 19**



**Model 22**



**Model V22**

WOODFORD



**Model 14, 16, 17, 19 Inlets**

Dia. X Min. Length Req'd. In Heated Area

|            |  |   |
|------------|--|---|
| <b>C</b>   |  | COMBINATION<br>Copper Sweat Fitting<br>1/2" K, L or M Inside<br>3/4" M Only Outside |
| <b>C1</b>  |  | 1/2" Copper Sweat Fitting   |
| <b>CP</b>  |  | COMBINATION<br>1/2" Male Pipe Thread<br>1/2" Female Sweat                           |
| <b>C3</b>  |  | 3/4" Female Sweat Fitting   |
| <b>P</b>   |  | COMBINATION<br>1/2" Female Pipe Thread<br>3/4" Male Pipe Thread                     |
| <b>PX</b>  |  | 1/2" PEX Tube Fitting   |
| <b>PX3</b> |  | 3/4" PEX Tube Fitting   |
| <b>W</b>   |  | 1/2" Wirsbo®/Uponor Tube Fitting  |
| <b>W3</b>  |  | 3/4" Wirsbo®/Uponor Tube Fitting  |
| <b>CM</b>  |  | COMBINATION<br>1/2" Compression Fitting<br>1/2" Copper Sweat Fitting                |


**Model 22 & V22 Inlets**

Dia. X Min. Length Req'd. In Heated Area

|            |  |   |
|------------|--|---|
| <b>C</b>   |  | COMBINATION<br>Copper Sweat Fitting<br>1/2" K, L or M Inside<br>3/4" M Only Outside |
| <b>CP</b>  |  | COMBINATION<br>1/2" Male Pipe Thread<br>1/2" Female Sweat                           |
| <b>C3</b>  |  | 3/4" Female Sweat Fitting   |
| <b>P</b>   |  | COMBINATION<br>1/2" Female Pipe Thread<br>3/4" Male Pipe Thread                     |
| <b>PX</b>  |  | 1/2" PEX Tube Fitting   |
| <b>PX3</b> |  | 3/4" PEX Tube Fitting   |
| <b>W</b>   |  | 1/2" Wirsbo®/Uponor Tube Fitting  |
| <b>W3</b>  |  | 3/4" Wirsbo®/Uponor Tube Fitting  |

## FREEZELESS: (Tube won't freeze when hose is detached)

Best Selling Residential Wall Faucet



MODEL 14

- No Anti-Siphon Protection
- Round, powder coated, die-cast aluminum handle

Packed 10 Per Master Carton

\*SUFFIX BP-Bulk pack cartons of 24 units are available on 4", 6", 8" 10" & 12" lengths ONLY.  
Plastic Handle (Suffix PH). Tee Key (Suffix TK)



MODEL 17

- Anti-Siphon Protected
- ASSE-1019-C Listed
- Round, powder coated, die cast aluminum handle

## ANTI-BURST: (Tube won't rupture even if hose is attached)


### Patented - PRV Pressure Relief Valve - Standard on models 16, 19, 22, V22 & C22

The patented, resetting PRV prevents the faucet tube from bursting in freezing conditions even if a hose is unintentionally left on.


The PRV protects up to 125 psi of backpressure and therefore does not require an add-on vacuum breaker.

Upgrade the Model 14 & 17 with RK-PRV Rod Assembly

Piston activates at approx. 350 psi



### PATENTED ANTI-BURST PRV



MODEL 16



MODEL 19  
With Anti-Siphon  
Protection

See Details  
On Page 27



BH Option 19

Packed 10 Per Master Carton

\*SUFFIX BP-Bulk pack cartons of 24 units are available on 4", 6", 8" 10" & 12" lengths ONLY.  
Tee Key (Suffix TK)

## HOT AND COLD FREEZELESS:

Optional DMP  
Drywall Mounting Plate.  
See Page 4 For Details.



MODEL 22



MODEL V22



BH Option 22

Packed 4 Per Master Carton

**WF-MS Wall Faucet Mounting Sleeve****- Boxed 10 to a carton -****FOR USE WITH MODELS 14, 16, 17 & 19 ONLY**

The WF-MS Wall Faucet Mounting Sleeve takes the guesswork out of how far to stub-out Woodford freezeless faucets through brick, stone or stucco veneers. Built-in anchors provides a secure installation for the faucet.

The 6" long Mounting Sleeve allows the plumber to determine a stub-in location and set an adjustable finish depth required by the brick or stone mason. A numbered scale, in 1/4" increments, is built into the top of the Mounting Sleeve.

The faucet installation is completed by mating the faucet wall flange to the front of the Mounting Sleeve and securing with two, furnished flange screws. The proper drain angle is automatically set by the rear Tube Rest.


**SL-17 Vandal Resistant Stem Lock****FITS WOODFORD MODELS: 14, 16, 17, 19, 22, & V22**

Easy to retrofit:


Replace the standard packing nut with furnished brass locking nut and snap on the Lock. 2 keys are included.

Easy access and operation:

1. Unlock and remove the Lock to reveal the faucet operating rod.
2. Use Tee Key to operate faucet.
3. Remove tee key, replace Lock.

**RK-OSF - Over Sized Flange****FITS WOODFORD MODELS: 14, 16, 17, 19 & 101**

- Fits behind an existing Woodford faucet flange to secure a loose fitting faucet or cover a larger opening in the wall.
- Requires 3/8" space behind original flange.



(4) Parts Including Fasteners In Kit

**DMP-Drywall Mounting Plate****USE WITH WOODFORD MODEL 22 OR V22 AND 122 OR V122 (MILD CLIMATE) MODELS.**

The DMP provides

- a secure anchor for the faucet
- clean and precise drywall installation
- fire retardant plastic

The DMP Mounting Plate can be configured in a horizontal or vertical position ready for faucet installation and plumbing hook-up.

Made from strong PC/ABS, the 4" X 9 1/4" Mounting Plate is designed to space the faucet wall flange away from 5/8" drywall just enough for finishing off with two mating Cover Plates leaving a durable and protective installation.

See website for installation instructions.

**RK-ADJ-PRV  
Adjustable Operating Rod  
Converts Faucet To Anti-Burst****FOR USE WITH MODELS 14, 16, 17, 19, 22 & V22**

- Adjustable Operating Rod assembles and adjusts for combinations of 4" to 14" model lengths in 2" increments.
- \*Includes the patented, resetting Pressure Relief Valve (PRV) upgrade. The PRV is designed to prevent the copper tube from bursting in freezing conditions *even if a hose is unintentionally left on*.
- Includes (4) all brass stems and (2) stainless steel clips plus (1) each replacement parts EPDM Packing, Packing Nut, Round Metal Handle and Handle Screw.
- *Complete instructions are provided with each RK-ADJ-PRV.*



Piston activates at approx. 350 psi

\*See PRV Details on page 3




**LAWN SPRINKLER SUPPLY**

- Provides outside access to water supply for easy start-up, winterizing and service
- Controls water service from the building exterior
- High flow rate and low pressure loss
- Head casting fits flush against an existing wall
- Pipe casing will pass through a 1-7/8" hole
- Outlet fittings included: 3/4" NPT
- Add feature -1IN to include 1" NPT
- Brass finish only
- Galvanized pipe casing





**OPTIONAL - Brass Pipe Casing**

Made To order - No Cancel No Return - Contact factory for pricing

**Optional 32-BF****Inlet descriptions****Model 25, 27, 30**

Dia. X Min. Length Req'd. In Heated Area

|            |   |
|------------|---|
| <b>C</b>   |  COMBINATION Copper Sweat Fitting 1/2" K, L or M Inside 3/4" M Only Outside<br>15/16" Dia X 1 5/8" |
| <b>CP</b>  |  COMBINATION 1/2" Male Pipe Thread 1/2" Female Sweat<br>15/16" Dia X 1 3/4"                        |
| <b>CP3</b> |  COMBINATION 3/4" Male Pipe Thread 3/4" Female Sweat<br>1 1/16" Dia X 1 7/8"                       |
| <b>P</b>   |  COMBINATION 1/2" Female Pipe Thread 3/4" Male Pipe Thread<br>1 1/16" Dia X 1 7/8"               |
| <b>PX</b>  |  1/2" PEX Tube Fitting<br>15/16" Dia X 1 3/4"                        |
| <b>PX3</b> |  3/4" PEX Tube Fitting<br>15/16" Dia X 1 3/4"                        |

**Rough-In Dimensions / O.A.L.****Model 25 or 27****Model 30****AUTOMATIC DRAINING • FREEZELESS • ANTI-BURST****Model 25**Model 34HA  
Anti-Siphon  
Vacuum Breaker  
ASSE 1019-B**Backflow Protected****Vandal Resistant Wall Faucets**  
Order the Model 25 or 27 with  
removable Tee Key (Suffix TK).**Model 27**With Patented High Flow  
Double Check  
50HA Backflow Preventer  
Field Testable  
ASSE 1052 Device  
No Sprayback**FREEZELESS WALL FAUCETS - AUTOMATIC DRAINING - Packed 10 Per Master Carton**  
Must specify Model, Inlet and Wall Thickness. Tee Key (Suffix TK)

**AUTOMATIC DRAINING • FREEZELESS • ANTI-BURST****Model 30 Backflow Protected****Inlet and Rough-In Dimensions shown on page 6**

The Woodford Model 30 faucet automatically drains with or without a hose attached. The faucet is designed for residential and light commercial outside water service applications.



- No sprayback when faucet is shut off
- All structural components made of brass
- No lead solder
- Oval, powder coated, die-cast aluminum handle
  - (Tee Key available)
- Max pressure: 125 p.s.i.
- Max Temperature: 120° F
- Model 30 wall faucet is ASSE 1053 Approved.
- Attached 50HA Backflow Preventer features:
- U.S. Patent No's. 8,042,565 & 8,272,394
- ASSE 1052 & UPC Listed
- High Flow Double Check

**Model 30 ONLY - Individual Carton Prices - Must specify Model, Inlet and Wall Thickness - Example: 30CP-6**

Tee Key (Suffix TK)

**Model 30 with -MS Mounting Sleeve - Individual Carton Prices**

Must specify Model, Inlet, Wall Thickness and MS - Example: 30CP-6-MS


Tee Key (Suffix TK)

**WF-30MS Mounting Sleeve ONLY**

The Woodford Model 30 Wall Faucet Mounting Sleeve (WF-30MS) takes the guesswork out of how far to stub-out Woodford Model 30 freezeless faucets through brick, stone or stucco veneers. It also provides a secure anchor for the faucet.

The 6" long Model 30 Mounting Sleeve allows the plumber to determine a stub-in location and set an adjustable finish depth required by the brick or stone mason. A numbered scale in 1/2" increments, is built into the top of the Mounting Sleeve.

The faucet installation is completed by mating the faucet wall flange to the front of the Mounting Sleeve and securing with two, furnished flange screws. The proper drain angle is built-in to the faucet head casting.

**MB30BX Modular Box System.. Includes Composite Box, Door & Fascia - Use****with the MODEL 30 - Not Included**

The Woodford Modular Box System (MB30BX) is designed to securely house a Model 30 wall faucet on residential buildings. The MB30BX includes a high impact composite box that is stubbed out of a frame or masonry wall. After the wall is finished, a durable composite door and fascia assembly is simply screwed into the box to create a secure access and an attractive front.

**Standard:** Thumb latch cylinder lock. **Optional:** Key (K) cylinder lock.

**RK-30MBDR****Replaceable Composite Door & Fascia Repair Kits**

- Shipped in individual carton
- Fits the MB30BX Modular Box
- Tan color
- (2) Lock options

**RK-30MBDR**  
Standard: Thumb Latch  
Cylinder Lock



**RK-30MBDR-K**  
Optional: Key (K) Cylinder Lock

**RK-Bracket**


RK-Bracket can be used to mount or support the box in a stud wall. Hole centers are provided on back of box for drilling (2) 9/32" holes. Bracket extends from 10" to 19".



Inlet and Rough-In Dimensions shown on page 9




## Model 65



ASSE 1019-B Listed  
With ASSE 1011  
Anti-Siphon  
34HA Vacuum Breaker  
Standard on B65 & RB65

## Model 67



On All Commercial  
Details On Page 27

With Patented High Flow  
Double Check  
50HA Backflow Preventer  
Field Testable; ASSE 1052 Device  
No Sprayback  
Standard on B67 & RB67

### WALL HYDRANTS & FACTORY ASSEMBLED Close Couple to 24"

### SQUARE (B) & ROUND (RB) BOX TYPE WALL HYDRANTS FREEZELESS / AUTOMATIC DRAINING / CHROME FINISH STANDARD

#### Must specify Model, Inlet and Wall Thickness

OPTIONAL FINISH Hydrants Only: Rough Brass (BR) - Polished Brass (PB) - N/A over 24" wall thickness.

OPTIONAL FINISH Square Box Only: Rough Brass (BR) - list each; Polished Brass (PB) -

Cylinder Lock Door: Specify Suffix (K) - Available on Chrome Square Box Only;

Flat door available for B65 ONLY (Suffix F) - N/C - Example: B65C-10-F;

Round Box -Chrome Finish Only. Order RB67BX (Bubble door only); N/A over 24" wall thickness.

## B65



## RB65



## B67



## RB67



Round Box models  
install through 6"  
diameter cored hole or  
6" Sch. 40 PVC sleeve.

NOTE: Chrome box assemblies are available to convert existing wall hydrant inventory to box type wall hydrants.

\*When converting to box type hydrant, deduct 2" from hydrant.

• EXAMPLE: B65-10" requires Box + 8" Model 65 or 67.

\*Order 65BXF to convert to flat door on square box type

\*Order 67BX to convert to box type B65 or B67

\*Order RB67BX to convert to round box type RB65 or RB67

## MB65 or MB67

## Modular Box Models

## MB65BX or MB65BX-K




2.6 pound, high impact, composite box with a replaceable 14 ga. stainless steel door and fascia assembly.

- MB65 or MB67: Modular box and Hydrant Assembly
- MB65BX: Modular Box, SS Door & Fascia Assembly Only
- RK-65MBDR: Stainless Steel Door & Fascia Repair Kit Assemblies (See Page 22 Door Assembly Repair Kits)

## Model 68 UNDERCOVER WALL HYDRANT®



- ASSE 1053 listed hydrant
- Integral, Flip-Down 16 ga. Stainless Steel Cover
- Sleek, streamlined design - only 1" protrusion from wall
- Vandal Resistant w/Tee Key Lock
- Chrome plated, flush mounted cast brass hydrant head
- Model 50 ASSE 1052 High Flow Double Check Backflow Preventer
- Automatically drains - even with hose attached



Must specify Model, Inlet and Wall Thickness  
OPTIONAL FINISH Hydrants Only: Rough Brass (BR)




On All Commercial  
Details On Page 27

Inlet and Rough-In Dimensions shown on page 9

HC67

Hot & Cold Mixers

HCB67



Includes Patented  
ASSE 1052 Nidel®  
50HA High Flow  
Double Check Backflow  
Preventer  
Field Testable and  
No Sprayback



N/A over 24" wall thickness

CHROME FINISH STANDARD


C22

Hot & Cold - Light Commercial

B22



Drywall Mounting Plate (DMP)  
Available for the C22. see page 4



Includes Patented ASSE 1052 Nidel® 50HA High low Double Check Backflow Preventer Field Testable and No Sprayback Includes (2) Patented PRV Pressure Relief Valves see page 3

CHROME FINISH STANDARD

(2) Brown Powder Coated Metal Handles (Suffix MH) - Tee Key (Suffix TK) B22 Available in Rough Brass (BR) - Box only (22BX)

### SL-65 Vandal Resistant Stem Lock

The SL-65 fits Models 65/67, B65/B67, RB65/RB67, MB65/MB67,  
70,74,76, 75, 79, 84 & 86 series products.

NOTE: The SL-65 **will not fit** in the B65 with Flat Door or the Model 68 Undercover™ Wall Hydrant.

Replace the standard packing nut with the furnished brass locking nut and snap on the lock. 2 keys are included.

A Tee key is included for operating the faucet when lock is removed.



### Model C22 & B22 Inlets - Dia. X Min. Length Req'd. In Heated Area

|           |   |           |   |            |  |
|-----------|---|-----------|---|------------|--|
| <b>C</b>  | COMBINATION Copper Sweat Fitting 1/2" K, L or M Inside 3/4" M Only Outside<br>7/8" Dia X 1 5/8" | <b>C3</b> | 3/4" Female Sweat Fitting<br>1 1/16" Dia X 1 7/8"     | <b>PX</b>  | 1/2" PEX Tube Fitting<br>7/8" Dia X 1 3/4" |
| <b>CP</b> | COMBINATION 1/2" MPT 1/2" Female Sweat<br>15/16" Dia X 1 3/4"                                   | <b>P</b>  | COMBINATION 1/2" FPT 3/4" MPT<br>1 1/16" Dia X 1 7/8" | <b>PX3</b> | 3/4" PEX Tube Fitting<br>7/8" Dia X 1 3/4" |

### Model 70 - Galvanized Pipe Casing



GALVANIZED PIPE CASING / CHROME FINISH STANDARD

OPTIONAL FINISH: Polished Brass (PB) - Brass (BR)

OPTIONAL - Brass Pipe Casing



Made To order - No Cancel No Return - Contact factory for pricing



P Inlet  
3/4"-14 FPT




C Inlet  
3/4" Copper Tube  
Solder Connection






## Model 65 & 67 Inlet Descriptions


**C Inlet**  
3/4" COPPER  
WATER TUBE




**P Inlet**  
3/4" FEMALE  
PIPE THREAD





### 65 & 67




### B65 & B67



### HC65 & HC67 ..... Hot & Cold ..... HCB65 & HCB67




### RB65 & RB67 ..... Round Box





Install using  
6" Dia. Core Drill

### C22 ..... Hot & Cold ..... B22




Optional for C22 & C22CC: Drywall Mounting  
Plate-DMP See description on page 5  
See Inlet Descriptions on page 8





On All Commercial  
Details On Page 27



## SRH-MS



## RHMC-MS



**Freezeless Roof Hydrants** are designed to facilitate a secure, exterior water source installation on commercial roof surfaces. The hydrant is installed through the roof and plumbed to the non-freezing interior water source. The hydrant is supported by a heavy duty cast iron (MS) Mounting System. All necessary mounting hardware for proper installation on a commercial roof is supplied, including a 2 degree shim for pitch adjustment.

Roof Hydrants are specified for washing condenser coils, windows, cooling towers, green roofs and other types of roof top equipment.

- Choose from 4 specific models.
- Order a complete Hydrant and Mounting System package or individual Hydrant or Mounting System units.
- All hydrants are operated by lifting the lever handle or turning a wheel handle.
- All repairs can be made from the top of the hydrant.

The patented **RHY1-1-MS** is the most reliable hydrant where backflow protection is not required. A 1/8" NPT tapped drain hole in valve body should be piped to a drain location to prevent freezing. *The user is not required to flush the hydrant.*

**ROOF HYDRANT**  
RHY1-1-MS (Complete)  
RHY1-1

The patented **RHY2-1-MS** features a built-in vent that allows automatic draining when hydrant is shut off, even with a hose and device attached. A 1/8" NPT tapped drain hole in the valve body should be piped to a drain location to prevent freezing. Includes ASSE 1052 Model 50HF Backflow Preventer. *The user is not required to flush the hydrant.*

**ROOF HYDRANT**  
RHY2-1-MS (Complete)  
RHY2-1

## ASSE 1057 SRH-MS Sanitary Roof Hydrant

ASSE 1057  
ASSE 1057

*NO Drain Line Required!*  
*This hydrant does not require removal of vacuum breaker or use of a diverter to protect from freezing.*

With hose removed, a venturi action draws water out of the internal reservoir and discharges through the outlet. Note: Special operating instructions to insure proper evacuation. Includes ASSE 1052 Model 50HF Backflow Preventer.

**ROOF HYDRANT**  
SRH-MS (Complete)  
SRH

The **RHMC-MS Mild Climate Roof Hydrant** is an excellent choice in non-freezing environments. The shut-off valve is located in the hydrant head and is wheel handle operated. Includes ASSE 1052 Model 50HF Backflow Preventer.












**ROOF HYDRANT**  
RHMC-MS (Complete)  
RHMC

The **cast iron RH-MS Roof Hydrant Mounting System** can be ordered separately with all required hardware included.

**ROOF HYDRANT**  
RH-MS



## RHY1-1-MS RHY2-1-MS



Inlet and Rough-In Dimensions shown on page 15

## Model 101 Residential



101C



101CP



101P



101PX

- ASSE 1019-Type C Listed
- Anti-siphon protection with integral check valve and atmospheric vent
- Eliminates the need for an add-on vacuum breaker
- Choose from five inlet options
- Round, powder coated, die-cast aluminum handles - Standard
- Wall flange is included with all models

### MODEL

101C - 1/2" & 3/4" Copper Sweat Inlet

101CP - 1/2" MPT & 1/2" Sweat Inlet

101P - 3/4" MPT & 1/2" FPT Inlet

101PX - 1/2" Pex Tube Inlet

101CM - 1/2" Compression Fitting/Copper Sweat

Suffix-BP-Bulk Pack Cartons of 6 units are available

## Model 122 & V122 Hot & Cold Residential



122



V122

- ASSE 1019-Type C Listed
- Anti-siphon protection with integral check valve and atmospheric vent
- Eliminates the need for an add-on vacuum breaker
- Choose from five inlet options
- (2) Oval, powder coated, die-cast aluminum handles - Standard

### MODEL

122C or V122C - 1/2" & 3/4" Copper Sweat Inlet

122CP or V122CP - 1/2" MPT & 1/2" Sweat Inlet

122P or V122P - 3/4" MPT & 1/2" FPT Inlet

122PX or V122PX - 1/2" Pex Tube Inlet

122CM or V122CM - 1/2" Compression Fitting/Copper Sweat

## Model 30CC Residential




The optional MB30BX can be used with the Model 30CC. See page 5 for details.

- Close Coupled version of the freezeless Model 30
- ASSE 1053 Backflow Protected, **Automatic Draining**; UPC, cUPC Approved
- ASSE 1052 Nidel® Model 50HA High Flow Double Check Backflow Preventer
- Fits within a 2 X 4 stud wall and
- Drains automatically with or without an attached hose
- Available with a composite box, door and fascia.


### MODEL

30CC (CP or PX Inlet Optional)

SL-17 Stem Lock for the Model 30 (Shown on page 4)



## Model MB221, MB224, MB226 Commercial



- Integral water supply stop is located at the faucet head
- 1/2-14 FPT Inlet connects through side of box
- Modular Box and Stainless Steel Door (3.3 lbs)
- Door Lock: Tee Key or Cylinder Lock (K)

### MODEL

MB221 Offers No Anti-Siphon Protection

MB224 Includes Single Check Vacuum Breaker

MB226 Includes 50HF Backflow Preventer

\*Key Cylinder Lock (Suffix K)

## Model C22CC, B22CC Hot & Cold Commercial



C22CC



B22CC

- Chrome plated brass head
- ASSE 1052 Nidel® Model 50HA High Flow Double Check Backflow Preventer

### MODEL

C22CC (CP & PX Inlet Optional)

B22CC (CP & PX Inlet Optional) - Box Type

### O.A.L.

2 3/4"

6 1/8"

(2) Brown Powder Coated Metal Handles (Suffix MH) - Tee Key (Suffix TK) - B22 Available in Rough Brass (BR)

B22CC Available in Rough Brass; B22 (BR) Box only (22BX)



*Inlet and Rough-In Dimensions shown on page 15*

**21, 24, 26, Y24/Y26 Series**

- 21 Series: Hose Nozzle outlet with No Anti-Siphon Protection
- 24 Series: ASSE 1011 Nidel® 34HF Single Check Vacuum Breaker
- 26 Series: ASSE 1052 Nidel® 50HF High Flow Double Check Backflow Preventer
- Standard: Clear Polycarbonate Wheel Handle & Tee Key; Optional: metal Wheel Handle Only (Does Not Include Tee Key)
- Standard Finish: Rough chrome; Optional: Rough brass (BR); Polished Chrome (PC)



**Inlet Options:**

- P1/2 = 1/2" FPT
- P3/4 = 3/4" FPT
- C = Combination 1/2" and 3/4" Copper Sweat
- CP = Combination 1/2" MPT and 1/2" Copper Sweat

**SL-24 Stem Lock**



Optional: SL-24 Vandal Resistant Stem Lock is available for all 21, 24, 26 & B26 models. See page 4 for Stem Lock details.



| MODEL                            | FEATURES                               | ROUGH BRASS | ROUGH CHROME    | POLISHED CHROME |
|----------------------------------|--|-------------|-----------------|-----------------|
|                                  |  | Add (BR)    | Standard Finish | Add (PC)        |
| 21P1/2 or 21P3/4                 | 3/4" Hose Nozzle                       | Add (BR)    | Standard Finish | Add (PC)        |
| 21C or 21CP                      | 34HF Single Check or 50HF Double Check | Add (BR)    | Standard Finish | Add (PC)        |
| 24P1/2, 24P3/4, 26P1/2 or 26P3/4 |  | Add (BR)    | Standard Finish | Add (PC)        |
| 24C, 24CP, 26C or 26CP           |  | Add (BR)    | Standard Finish | Add (PC)        |
| Y24 or Y26                       |  | Add (BR)    | Standard Finish | Add (PC)        |
| SL-24                            | Stem Lock - Chrome/Gray                |             |                 |                 |

**MB24, MB26, MB24BX Modular Wall Box System**

- Includes Composite Box, 14 gauge Stainless Steel Door & Fascia
- Order with or without a Model 24P or 26P faucet. See pricing below
- Faucet includes Wheel Handle & Tee Key
- Standard Faucet Finish: Rough chrome.
- Standard: Tee Key latch
- Key Cylinder Lock (Suffix K)




| MODEL              | FEATURES   |
|--------------------|--|
| MB24-1/2 or 3/4    | with composite box, SS door and fascia and ASSE 1011 34HF vacuum breaker     |
| MB26-1/2 or 3/4    | with composite box, SS door and fascia and ASSE 1052 50HF backflow preventer |
| MB24BX (No Faucet) | Modular Box System ONLY; composite box, SS door and fascia                   |

**B24, B26, Metal Wall Box Option**

- Order with a Model 24P or 26P faucet. See pricing below
- Standard: Chrome Plated Brass Box & Door; Optional: Rough brass (BR); Polished Brass (PB)
- Standard: Wall Faucet Wheel Handle & Tee Key; Optional: Metal Handle Only (MH)
- Standard: Tee Key latch



Box is drilled for optional mounting bracket. Order: RK-Bracket Page 19  
Use to mount B24 & B26 or MB24 & MB26



| MODEL           | FEATURES   |
|-----------------|--|
| B24-1/2 or 3/4  | with chrome plated brass box and ASSE 1011 34HF vacuum breaker     |
| *B26-1/2 or 3/4 | with chrome plated brass box and ASSE 1052 50HF backflow preventer |
| B24BX           | B24 Box w/Flat Door (B24BX) .....                                  |
| B26BX           | B26 Box w/Bubble Door (B26BX) .....                                |

OPTIONAL FINISHES: Rough Brass (BR) - Polished Brass (PB)

\*Metal Handle Available on B26 Only (Suffix MH) Optional;

B26 Box w/Bubble Door (B26BX)

B24 Box w/Flat Door (B24BX)

## 70 & 80 Series Close Coupled



- Loose Tee Key operated
- Rectangular, recessed or flush mounting chrome plated brass heads
- 3 Inlet options
- All models fit inside a 4" wall
- Choose single check or double check models
- All hydrants are available with rectangular or round brass box and door
- Standard Finish: Chrome
- Optional Finish: (Extra charge) Rough Brass (BR) Polished Brass (PB)

The unique design of the Model 75 and 79 allows the installer to rotate the 3/4" FPT inlet by hand to easily complete connection regardless of direction.

**Model 75**  
ASSE 1011



**Model 79**  
ASSE 1052



### MODEL FEATURES

|    |   |
|----|---|
| 75 | ASSE 1011 34HF vacuum breaker and swivel inlet with adjustable 360° orientation     |
| 79 | ASSE 1052 50HF backflow preventer and swivel inlet with adjustable 360° orientation |

OPTIONAL FINISH: Rough Brass (BR) - Polished Brass (PB)



**Model 74**  
ASSE 1011



**Model 76**  
ASSE 1052



**Model 84**  
ASSE 1011



**Model 86**  
ASSE 1052

### MODEL FEATURES

|          |  |
|----------|--|
| 74C, 74P | with straight nozzle and ASSE 1011 34HF vacuum breaker     |
| 84C, 84P | with angled nozzle and ASSE 1011 34HF vacuum breaker       |
| 76C, 76P | with straight nozzle and ASSE 1052 50HF backflow preventer |
| 86C, 86P | with angled nozzle and ASSE 1052 50HF backflow preventer   |

OPTIONAL FINISH: Rough Brass (BR) - Polished Brass (PB)



**Model B74 or B75**  
ASSE 1011

**Model B76 or B79**  
ASSE 1052



Mounting Bracket Included

**Model RB74 or RB75**  
ASSE 1011

**Model RB76 or RB79**  
ASSE 1052



### RECTANGULAR BOX      ROUND BOX      FEATURES

|           |            |   |
|-----------|------------|---|
| B74C or P | RB74C or P | with straight nozzle and ASSE 1011 34HF vacuum breaker          |
| B75       | RB75       | with ASSE 1011 34HF vacuum breaker (360° Inlet orientation)     |
| B76C or P | RB76C or P | with straight nozzle and ASSE 1052 50HF backflow preventer      |
| B79       | RB79       | with ASSE 1052 50HF backflow preventer (360° Inlet orientation) |

#### MOUNTING BRACKET INCLUDED


Flat door available for B74 or B75 ONLY - (Suffix F)

OPTIONAL FINISH: Rough Brass (BR) - Polished Brass (PB)

Cylinder Lock Door: Specify (Suffix K) (Available in Chrome Square Box Only)


Order 74BX box assembly to convert to box type B74, B75, B76, B79

## Rough-In Dimensions




**Model 74 & 76**

C Inlet - 3/4" Female Copper Sweat  
P Inlet - 3/4" FPT




**Model 75 & 79**

3/4" FPT  
360° Swivel Inlet




**Model 84 & 86**

C Inlet - 3/4" Female Copper Sweat  
P Inlet - 3/4" FPT



**B74 & B76**

**B75 & B79**



**RB74 & RB76**

**RB75 & RB79**



## V26 Vertical

The Model V26 is an anti-siphon, vacuum breaker protected wall faucet designed for irrigation purposes in mild climate areas. The Model V26 is designed to be mounted directly to a wall or column with a top mount inlet. Designed to blend with modern architecture for installation on or in service stations, custodial services, churches, motels, restaurants, etc.

### SPECIFICATIONS:

#### VACUUM BREAKER - ANTI-SIPHON:

- NIDEL® Model 50HF with  $\frac{3}{4}$  inch male hose thread
- ASSE Standard 1052 approved
- IAPMO® listed

**EPDM PACKING:** Prevents leaking.

**PACKING NUT:** Adjustable brass nut with deep stem guard.

**VALVE SEAT:** Standard "O" size washer.

**HANDLES:** Furnished with tan plastic wheel handle and loose tee key.

**INLET:**  $\frac{1}{2}$  FPT.

**MAX PRESSURE:** 125 p.s.i.

**MAX TEMPERATURE:** 120° F



**SHIPPING WEIGHT:** (per unit): 1.4 lb

**EXTERIOR FINISH:** Rough Brass (BR) or Chrome (CH)


## Model V26



### Mild Climate Series Rough-In Dimensions



All Yard Hydrants include a 1/8" NPT drain hole in the valve body.




| 3/4" INLETS         |           |
|---------------------|-----------|
| Y30BR               | (1)       |
| Y30CH               | (1)       |
| Y34                 | (1)(3)    |
| Y34 Stainless Steel | (5)       |
| Y95                 | (1)(2)(4) |
| 1" INLETS           |           |
| Y1                  | (1)(3)    |
| Y2                  | (1)(4)    |

- (1) Brass pipe casing and operating pipe available. Contact factory for pricing.
- (2) Polished brass Suffix PB finish: call for pricing
- (3) One Inch Hose Nozzle Suffix HN 26.15
- (4) Backflow Protected - ASSE 1052 Model 50HF Backflow Preventer
- (5) Add -Suffix SS option for Stainless Steel\*


All Hydrants shipped with Head Cover - Add - Suffix BX for Box

\*\* 6' and longer must be shipped Freight/LTL



All Yard Hydrants include a 1/8" NPT drain hole in the valve body.

U34A U75M U100M U100W U125A U125W



#### 3/4" INLETS

U34 Spout | (1)

#### 1" INLETS

U75 Tee | (1)

(1) Specify Suffix "A" (Automatic Close Handle), "M" (Manual Close Handle)

(2) Specify Suffix "A" (Automatic Close Handle), "M" (Manual Close Handle), "W" (Wheel Handle)

(3) Specify Suffix "M" (Manual Close Handle), "W" (Wheel Handle)

\*\* 6' and longer must be shipped Freight/LTL

#### 1 1/4" INLETS

U100 | (2)

#### 1 1/2" INLETS

U125 | (2)

#### 1 1/2" INLETS

U150 | (3)

#### 2" INLETS


U200 | (3)

U150M

U150W

U200M

U200W



All hydrants on this page comply with Safe Drinking Water Act effective 1/4/2014

## Model S3 & S4H



**Freezeless, Low Lead, Sanitary** Yard Hydrants are designed to produce immediate water flow in sub-zero temperatures.

- Specify for use in public areas such as camp grounds and parks or any location where low lead hydrants are required
- Hydrants are completely sealed to prevent ground water from entering the reservoir or service line

- Divertor spout allows independent water flow when hose is attached to backflow preventer
- The S4H meets ADA requirements for height and 5 lbs. maximum operating force
- \*\* 5' and longer must be shipped Freight/LTL

**OPTIONAL: ASSE 1057 Approved Device - Single Check Vacuum Breaker (Suffix SC)**

S3 - Manual Close - Backflow Protected

S4H - ADA Compliant - SELF CLOSING - Backflow Protected

See web site for verification sheet

## Thermaline®



**The Thermaline®, Low Lead, Sanitary** Water Connector is a compact unit especially designed to provide water service to mobile homes in freezing conditions.

- Ideal wherever a freezeless sanitary tight line installation is needed, such as, waterers for livestock
- High strength plastic casing is insulated with permanently molded and bonded polyurethane foam

- 2 foot, 15 watt (110-120v) portable insert heater is standard on 2' - 6' hydrants
- 4 foot, 30 watt (120v) portable insert heater is optional on 6' hydrants and standard on 7' and longer hydrants
- Costs about a penny a day to operate even at 50° below zero
- Wheel handle at surface level shuts off water below the frost line when hydrant is not in use

Brass pipe casing and operating pipe available. Contact factory for pricing.

Available without heating element (Suffix NE)

Optional 6' Thermaline® with 4' Heater

## H34



**The Model H34, Low Lead, Sanitary** is a non-draining hydrant that features a thermostatically controlled heating element that prevents water in the hydrant from freezing even at temperatures down to 20 degrees below zero.

- One foot bury depth closed system design

### MODEL

H34 3' long cord standard

H34-C12 Includes 12' cord

H34-C25 Includes 25' cord


One Length Required. 1" MPT Male Thread Inlet

### S3


### S4H

### THERMALINE®

### H34



## Hose Connection Nidel® Vacuum Breakers & Backflow Preventers



34HA standard on Model 25 & 65; 34HF standard on Model 24, 43, 44, 45, 46, 74, 75, 84  
 50HA standard on Model 67; 50HF standard on Model 76, 79, 86

\* 55180 Nozzle Required;

\*\* Converts Model 65 to Model 67

### Double Check ASSE 1052

| INTEGRAL DEVICES |       |      |
|------------------|-------|------|
| FINISH           | *50HA | 50HF |
| BRASS (BR)       |       |      |
| CHROME (CH)      |       |      |

50HA replaces VB222 and is standard on Model C22, B22, 27, 30 & 67

50HF standard on Model 26, Y2, H34, B26, Y95


\* Converts Model 65 to Model 67



### \*Patented High Flow Double Check Model 50 Backflow Preventer

The first ASSE 1052 Approved automatic draining high flow double check backflow preventer.

When a hose is removed from a Model 50 equipped wall faucet or yard hydrant, two linked but independent checks move as one to open a path through the valve allowing water to drain completely and prevent freezing.



## Repair Kits

### RK-14/17MH

METAL WHEEL  
HANDLE  
**8 SPLINES**



1. 30096 Wheel Handle-Metal
2. 30002 Handle Screw

### RK-25/27H

MODEL 25 & 27  
WHEEL HANDLE  
**5/16 SQUARE SHANK**

1. 30239 Wheel Handle
2. 30234 Handle Screw



### RK-Bracket

MOUNTING  
BRACKET  
FOR BOX TYPE  
HYDRANTS



### RK-17VB

MODEL 17  
VACUUM  
BREAKER  
FLOAT KIT



### RK-19VB

MODEL 19  
VACUUM  
BREAKER  
FLOAT KIT



### RK-101VB

MODEL 101  
VACUUM  
BREAKER  
FLOAT KIT



### RK-22VB

MODEL 22 &  
V22  
VACUUM  
BREAKER  
FLOAT KIT



### RK-122VB


MODEL 122 &  
V122  
VACUUM  
BREAKER  
FLOAT KIT



**RK-14MH**

**MODEL 14/18  
METAL HANDLE**

1. 30002 Handle Screw
2. 30096 Wheel Handle (Metal)
3. 30059 Packing Nut
4. 30560 EPDM Packing
5. 30006 Packing Support Washer
6. 30008 Valve Seat Rubber
7. 30009 Retainer Screw




**RK-17MH**

**MODEL 17  
METAL HANDLE**

1. 30002 Handle Screw
2. 30096 Handle (Metal)
3. 30059 Packing Nut
4. 30560 EPDM Packing
5. 30421 Packing Washer
6. 30418 Check Valve
7. 30008 Valve Seat Rubber
8. 30009 Retainer Screw
9. RK-17VB Float Kit
10. 30459 Bevel Check Valve


Use for faucets dated 04/98 or later.  
See packing nut.



**RK-19**

**MODEL 19**


1. 30002 Handle Screw
2. 30559 Oval, Die Cast Aluminum Wheel Handle
3. 30059 Packing Nut
4. 30560 EPDM Packing
5. 30421 Packing Support Washer
6. 30459 Check Valve
7. 30008 Valve Seat Rubber
8. 30804 Retainer Screw
9. RK-19VB Float Kit



**RK-PRV**

**PRESSURE RELIEF VALVE  
UPGRADE KIT FOR MODEL 14 & 17**

1. 30002 Handle Screw
2. 30096 Round Metal Handle
3. 30059 Packing Nut
4. 30560 EPDM Packing
5. Valve Stem Assembly (See Chart)



| Wall Thickness | Overall Length |
|----------------|----------------|
| RK-PRV-4       | 5 7/8"         |
| RK-PRV-6       | 7 7/8"         |
| RK-PRV-8       | 9 7/8"         |
| RK-PRV-10      | 11 7/8"        |
| RK-PRV-12      | 13 7/8"        |
| RK-PRV-14      | 15 7/8"        |
| RK-PRV-16      | 17 7/8"        |
| RK-PRV-18      | 19 7/8"        |
| RK-PRV-20      | 21 7/8"        |
| RK-PRV-22      | 23 7/8"        |
| RK-PRV-24      | 25 7/8"        |

\* Insert wall thickness.  
Example for 10" wall thickness:  
RK-PRV-10


**RK-25**

**MODEL 20/25/27**

1. 30234 Handle Screw
2. 30239 Wheel Handle
3. 30241 Head Nut
4. 30236 Drain Guard
5. 30245 Headnut Gasket
6. 30238 Stem Screw
7. 35280 Drain Valve Assembly
8. 30230 Plunger Assembly

**RK-27**


**MODEL 25/27 includes  
50HA-BR no backspray**



**RK-30**

**MODEL 30**

1. 30002 Handle Screw
2. 30559 Oval, Die Cast Aluminum Wheel Handle
3. 30059 Packing Nut
4. 30264 Stem Screw
5. 30105 Packing Washer
6. 35281 Drain Valve Assembly
7. 30260 Plunger Assembly



**RK-ADJ-PRV**

**ADJUSTABLE OPERATING ROD  
MODEL 14, 16, 17, 19, 22, V22**

1. 35124 Inlet Stem
2. 35123 Middle Stem
3. 35122 Handle Stem
4. 30508 Stem Stop
5. Stainless Steel Clips (2)
6. 30560 EPDM Packing
7. 30059 Packing Nut
8. 30096 Round Metal Wheel Handle
9. 30002 Handle Screw




- Adjustable Operating Rod assemblies for 4" to 14" model lengths in 2" increments.
- Includes the patented, resetting Pressure Relief Valve (PRV) upgrade.
- Complete instructions are provided with each RK-ADJ-PRV.



**RK-22MH MODEL 22/V22 HOT AND COLD METAL HANDLE**

1. 30566 Hot Plug Button
2. 30002 Handle Screw (2)
3. 30096 Round, Die Cast Alum. Wheel Handle (2)
4. 30059 Packing Nut (2)
5. 30560 EPDM Packing (2)
6. 30006 Packing Washer (2)
7. 30565 Cold Plug Button
8. 30459 Check Valve (2)
9. 30008 Valve Seat Rubber (2)
10. 30009 Retainer Screw (2)

Operating Rod Not Included




CHROME PARTS AVAILABLE UPON REQUEST AT ADDITIONAL CHARGE.  
Remove operating rod to service internal parts.

**RK-22PRV MODEL 22/V22 HOT AND COLD 2008 Vent Float Design**

1. 30566 Hot Plug Button
2. 30002 Handle Screw (2)
3. 30559 Oval, Aluminum Handle (2)
4. 30059 Packing Nut (2)
5. 30560 EPDM Packing (2)
6. 30421 Packing Washer (2)

Operating Rod Not Included




Remove operating rod to service internal parts.

**RK-101**

**MODEL 101**

1. 30002 Handle Screw
2. 30096 Round, Die Cast Alum. Wheel Handle
3. 30570 Packing Nut - Model 101
4. 30247 EPDM Packing
5. 30105 Packing Support Washer
6. 30824 Anti-Turbulence Sleeve
7. 30459 Check Valve
8. 30008 Valve Seat Rubber
9. 30009 Retainer Screw
10. RK-101VB Vacuum Breaker Float Kit




Stem Screw Not Included

**RK-32**

**MODEL 32 SPRINKLER SUPPLY**

1. 50611 AS-124 O-ring
2. 30107 Packing Nut-brass
3. 30247 EPDM Packing
4. 55176 Head Nut Assembly
5. 50035 1/4" Pipe Plug
6. 51014 Yoke Nut
7. 50027 Plain Washer
8. 51013 Ball Valve Rubber
9. 50028 Round Brass Nut




Operating Rod Not Included

**RK-122**

**MODEL 122 & V122**

1. 30566 Plug Button-H-Red
- 1a. 30565 Plug Button-C-Blue
2. 30002 Handle Screw (2)
3. 30559 Oval, Die Cast Alum. Wheel Handle (2)
4. 30570 Packing Nut - Model 101 (2)
5. 30247 EPDM Packing (2)
6. 30105 Packing Support Washer (2)
7. 30824 Anti-Turbulence Sleeve (2)
8. 30459 Check Valve (2)
9. 30008 Valve Seat Rubber (2)
10. 30009 Retainer Screw (2)
11. RK-122VB Vacuum Breaker Float Kit

Stem Screw Not Included




**RK-OSF**

**MODEL 14, 16, 17, 19, 101 Over Sized Flange**

1. 30091 Oversized Flange - Top
2. 30092 Over Sized Flange - Bottom
3. 30234 Mounting Screw (2)

Fits behind an existing Woodford Faucet flange to secure a loose fitting faucet or cover a larger opening in the wall.




**RK-65**

**MODEL 60 / 65 / 67 / 68**

**CHROME**


1. 50009 Tee key
2. 50264 Head Nut
3. 50252 Stem Washer
4. 55062 Stem Screw
5. 50251 "C" Washer
6. 51014 Yoke Nut
7. 50250 Plunger



**RK-68DR**

**MODEL 68 DOOR CHROME**

1. 30139 Tee Key Lock
2. 30156 Tee Key Lock Disc Spring
3. 30140 Tee Key Lock Well
4. 30143 Cam Lock
5. 30150 Cam Screw
6. 30155 Hex Nut
7. 50280 SS Head Cover
8. 50041 Headless Shoulder Bolt (2)




**RK-70**

**MODEL 70 & 72**

**WALL HYDRANT-CHROME**

Obsolete Models 7/8/80/85/90/95

1. 50009 Tee key
2. 30109 Packing Nut
3. 30247 Packing
4. 55177 Head Nut Assy.
5. 51014 Yoke Nut
6. 50027 Support Washer
7. 51013 Ball Valve Rubber
8. 50028 Round Brass Nut



**RK-75**

**MODEL 75/B75/79/B79 CLOSE COUPLED WALL HYDRANT CHROME**


1. 50009 Tee key
2. 30109 Packing Nut
3. 30247 Packing
4. 55183 Head Nut Assy. (1 29/32" O.A.L.)
5. 55105 Yoke Nut/Valve Assy.



**RK-HC**

**MODEL HC/HCB HOT & COLD WALL HYDRANT**

1. 51092 O-Ring AS-110
2. 51093 O-Ring AS-023
3. 50529 Packing Support Washer
4. 50502 Gasket (2)
5. 55079 Shuttle Housing Assy. (2)



WOODFORD



**DOOR ASSEMBLY REPAIR KITS**

|             |                        |
|-------------|------------------------|
| RK-65DR*    | B65 Flat Door-Chrome   |
| RK-65DR-BR* | B65 Flat Door-Brass    |
| RK-67DR*    | B67 Bubble Door-Chrome |
| RK-67DR-BR* | B67 Bubble Door-Brass  |
| RK-24DR     | B24 Flat Door-Chrome   |
| RK-24DR-BR  | B24 Flat Door-Brass    |
| RK-26DR     | B26 Bubble Door-Chrome |
| RK-26DR-BR  | B26 Bubble Door-Brass  |

All door assemblies include: (1) Door, (1) E Ring, (1) Door Lock Screw, (2) Hinge Pins

**MODULAR DOOR & FASCIA ASSEMBLIES**

|            |                      |
|------------|----------------------|
| RK-30MBDR* | MB30 Composite       |
| RK-24MBDR* | MB24 Stainless Steel |


All modular door assemblies include: (1) Door, (1) Fascia, (1) Hinge Rod, (2) Hinge Screws, (2) Hinge Washers, (1) Spring

\*Optional: Key (K) Cylinder Lock (Add \$25.00 to List)

Note: Original unit must have -K on B65/B67

**RK-24**

**MODEL 21/24/B24/26/B26/Y24/Y26/V26/40 CHROME**



1. 30121 Handle Screw
2. 30120 Wheel Handle
3. 30109 Packing Nut
4. 30247 EPDM Packing
5. 30105 Packing Washer
6. 30104 Operating Screw
7. 30008 Valve Seat Rubber
8. 30009 Retainer Screw

**RK-71**

**MODEL 71/74/76/81/84/86**

**B71/B74/B76**

**CLOSE COUPLED WALL HYDRANT CHROME**

1. 50009 Tee key
2. 30109 Packing Nut
3. 30247 Packing
4. 55177 Head Nut Assy. (2 1/4" O.A.L.)
5. 55105 Yoke Nut/Valve Assy.



**RK-40HT**

**MODEL 40HT HALF TURN**

1. 30247 Packing
2. 30105 Packing Washer
3. 30008 Valve Seat Washer
4. 30009 Seat Rubber Screw

*Stem Screw Not Included*

**RK-40SC**

**MODEL 40SC SELF CLOSE**

1. 30523 Head Nut Gasket
2. 30520 O-Ring (2)
3. 30526 Retaining Pin
4. 30008 Valve Seat Rubber
5. 30009 Seat Rubber Screw


*Stem Screw Not Included*

## Y34 &amp; Y1 HEAD ASSEMBLY

## RK-Y34HA (15003)

1. 15004 Y34 Head
2. 10104 Rod Stem
3. 10100 Packing Nut
4. 10101 Packing
5. 10102 Support Washer
6. 10011 Reducing Coupling
7. 10206 Hex Nut (3)
8. 10009 Upper Link

9. 15007 Lower Link (Includes Item 11)
10. 10019 Set Screw (2)
11. 15008 Cam & Clevis Assembly
12. 10020 Link Bolt (2)
13. 10021 Lever Bolt
14. 10008 Lever
15. 10004 3/4" Brass Hose Nozzle Head Casting #106



## RK-Y1HA (15001)

1. 15002 Y1 Head
2. 10100 Packing Nut
3. 10101 Packing
4. 10102 Packing Support Washer
5. 10104 Brass Rod Stem
6. 10011 Reducing Coupling
7. 10206 Hex Nut (3)
8. 10009 Upper Link

9. 15007 Lower Link (Includes Item 11)
10. 10019 Set Screw (2)
11. 15008 Cam & Clevis Assembly
12. 10020 Link Bolt (2)
13. 10021 Lever Bolt
14. 10008 Lever
15. 10007 1" Brass Hose Nozzle Head Casting #105

## RK-Y34

## MODEL Y34 YARD HYDRANT

Head Casting #106



1. 10104 Rod Stem
2. 10100 Packing Nut
3. 10101 Packing
4. 10102 Support Washer
5. 10105 Plunger

RK-Y1 MODEL Y1, Y2, S3, YARD HYDRANT  
RHY1, RHY2 ROOF HYDRANT

1. 10104 Rod Stem
2. 10100 Packing Nut
3. 10101 Packing
4. 10102 Support Washer
5. 10106 Plunger

## RK-YHL

MODEL Y1/Y2/Y34  
YARD HYDRANT LINKS

1. 10206 Hex Nut (3)
2. 10009 Upper Link (orange)
3. 15007 Lower Link Assy. (orange)
4. 15008 Cam & Clevis Assy. (orange)
5. 10020 Link Bolt (2)
6. 10021 Lever Bolt

## RK-SHL


MODEL S3 SANITARY  
YARD HYDRANT LINKS

1. 10206 Hex Nut (3)
2. 10444 Upper Link (blue)
3. 15211 Lower Link Assy. (blue)
4. 15241 Cam & Clevis Assy. (blue)
5. 10020 Link Bolt (2)
6. 10021 Lever Bolt

## RK-RHL

MODEL RHY1/RHY2  
ROOF HYDRANT LINKS

1. 10206 Hex Nut (3)
2. 10614 Upper Link (gray)
3. 15242 Lower Link Assy. (gray)
4. 15243 Cam & Clevis Assy. (bronze)
5. 10020 Link Bolt (2)
6. 10021 Lever Bolt




## RK-W34

W34 YARD HYDRANT  
(ORANGE HEAD)

## RK-X34

X34 YARD HYDRANT  
(BLUE HEAD)

1. 15050 Pivot Assembly
2. 10104 Rod Stem
3. 10100 Packing Nut
4. 10101 Packing
5. 10102 Support Washer
6. 10105 Plunger (W34)
6. 10108 Plunger (X34)

RK-WXL  
MODEL W34/X34  
STEEL LINK

## RK-R34

## R34 YARD HYDRANT


1. 10620 Link Plates (2)
2. 10619 Pivot Square
3. 10588 Rod Stem
4. 10100 Packing Nut
5. 10101 Packing
6. 10102 Packing Support Washer
7. 10108 Plunger

OTHER YARD  
HYDRANT FULL  
HEAD ASSEMBLIES

RK-X34HA  
RK-W34HA  
RK-R34HA

**RK-Y95**

MODEL Y70/Y95  
BOX TYPE YARD HYDRANT



**RK-Y30**

MODEL Y30  
POST TYPE YARD HYDRANT



**RK-THERM**




THERMALINE  
HEATED, INSULATED  
SANITARY YARD HYDRANT

**RK-TL-1H**

THERMALINE  
HEATER & HEATER WELL

**RK-TL-2H**

**RK-TL-4H**



Heater Assembly w/Heater Cover

85061..... 1'

85062..... 2'

85065..... 4'

All Heater Assemblies  
Include:  
(1) 80061 Heater Cover


**RK-H34**



MODEL H34  
HEATED, BACKFLOW PROTECTED  
SANITARY YARD HYDRANT


**RK-HTR**

H34 HEATER ASSEMBLY



**RK-SRH**



MODEL SRH  
SANITARY ROOF HYDRANT



**RK-RHMC**

MODEL RHMC  
ROOF HYDRANT  
MILD CLIMATE





**MODEL 10**

| PART # | DESCRIPTION                        |
|--------|------------------------------------|
| 10112  | Handle Screw                       |
| 10113  | Stem Screw                         |
| 50023  | Wheel Handle                       |
| 50024  | Packing                            |
| 50064  | Support Washer                     |
| 74527  | Packing Support Washer             |
| 74528  | Valve Seat Rubber                  |
| 74529  | Retainer                           |
| 74530  | Retainer Screw                     |
| 74532  | Yoke Nut                           |
| 74533  | Packing Nut                        |
| 74541  | Valve Stem Assy. 4" WT-6 3/4 OAL   |
| 74542  | Valve Stem Assy. 6" WT-8 3/4 OAL   |
| 74543  | Valve Stem Assy. 8" WT-10 3/4 OAL  |
| 74544  | Valve Stem Assy. 10" WT-12 3/4 OAL |
| 74545  | Valve Stem Assy. 12" WT-14 3/4 OAL |
| 74546  | Valve Stem Assy. 14" WT-16 3/4 OAL |
| 74547  | Valve Stem Assy. 18" WT-20 3/4 OAL |
| 74548  | Valve Stem Assy. 24" WT-26 3/4 OAL |

WT = Wall Thickness, OAL = Overall Length  
(5/16" Diameter Valve Stem Rod)

**MODEL 12**

| PART # | DESCRIPTION                      |
|--------|----------------------------------|
| 30002  | Handle Screw                     |
| 30005  | Packing                          |
| 30009  | Retaining Screw                  |
| 30107  | Packing Nut, Brass               |
| 74506  | Packing Support Washer           |
| 74509  | Valve Seat Rubber                |
| 74513  | Wheel Handle                     |
| 74517  | Rod Assembly 6" WT - 8 1/8 OAL   |
| 74518  | Rod Assembly 8" WT - 10 1/8 OAL  |
| 74519  | Rod Assembly 10" WT - 12 1/8 OAL |
| 74520  | Rod Assembly 12" WT - 14 1/8 OAL |
| 74521  | Rod Assembly 14" WT - 16 1/8 OAL |
| 74522  | Rod Assembly 18" WT - 20 1/8 OAL |
| 74531  | Rod Assembly 24" WT - 26 1/8 OAL |

WT = Wall Thickness, OAL = Overall Length  
(3/8" Diameter Rod - 16 Splines)



Order Repair Kit RK-70 for the  
Model 7, 8, 80, 85, 90 and 95 sold on page 22.

**MODEL 7**

| PART # | DESCRIPTION   |
|--------|---------------|
| 50070  | Head (Chrome) |

**MODEL 8**

| PART # | DESCRIPTION   |
|--------|---------------|
| 50078  | Head (Chrome) |
| 50079  | Head (brass)  |

**MODELS 77 & 78**


All parts available except deep box castings - Parts same as Y70 Hydrant or Model 70 and 80.




Model 80  
Woodford Freezeless



Model 85  
Woodford Freezeless  
Anti-Contamination  
34HW Vacuum Breaker  
(55180 Nozzle Required)



Model 90  
Woodford Freezeless



Model 95  
Woodford Freezeless  
Anti-Contamination  
34HW Vacuum Breaker  
(55180 Nozzle Required)

| PART  | DESCRIPTION             | WHERE USED                        | PART  | DESCRIPTION             | WHERE USED                           |
|-------|-------------------------|-----------------------------------|-------|-------------------------|--------------------------------------|
| 10004 | Hose Nozzle, 3/4"       | Y34, Y1, W34, X34, R34            | 30512 | Packing Nut w/Stem Gd.  | 14, 17                               |
| 10007 | Hose Nozzle, 1"         | Y34, Y1, W34, X34, R34            | 30559 | Oval Handle             | 19                                   |
| 10008 | Lever                   | Y34, Y1, Y2                       | 30560 | EPDM Packing            | 14, 17, 19, 22, V22                  |
| 10009 | Link, Upper             | Y34, Y1, Y2                       | 30565 | C - Plug Button-large   | 29                                   |
| 10011 | Coupling                | Y34, Y1, Y2, W34                  | 30566 | H - Plug Button-large   | 29                                   |
| 10018 | Valve Body              | W34, X34, Y30, Y34, Y70, Y95      | 35280 | Drain Valve Assembly    | 20, 25, 27                           |
| 10020 | Bolt                    | Y34, Y1, Y2                       | 35504 | Repl. Assy. 4" Wall     | 20, 25, 27                           |
| 10021 | Bolt                    | Y34, Y1, Y2                       | 35506 | Repl. Assy. 6" Wall     | 20, 25, 27                           |
| 10100 | Packing Nut             | Y34, Y1, Y2, W34                  | 35508 | Repl. Assy. 8" Wall     | 20, 25, 27                           |
| 10101 | Packing                 | Y34, Y1, Y2, W34                  | 35510 | Repl. Assy. 10" Wall    | 20, 25, 27                           |
| 10102 | Washer                  | Y34, Y1, Y2, W34                  | 35512 | Repl. Assy. 12" Wall    | 20, 25, 27                           |
| 10103 | Rod Stem                | Y34, Y1                           | 35720 | Rod Assy. 4" Wall       | 14, 17, 22, V22 (6" OAL w/ check)    |
| 10104 | Rod Stem                | Y34, Y1, Y2, W34                  | 35721 | Rod Assy. 6" Wall       | 14, 17, 22, V22 (8" OAL w/ check)    |
| 10105 | Plunger                 | Y30, Y34, Y70, Y95, W34           | 35722 | Rod Assy. 8" Wall       | 14, 17, 22, V22 (10" OAL w/ chk)     |
| 10106 | Plunger                 | Y1, Y2                            | 35723 | Rod Assy. 10" Wall      | 14, 17, 22, V22 (12" OAL w/ chk)     |
| 10107 | Plunger, 7/16-20 Thread | X34 - Yellow Head                 | 35724 | Rod Assy. 12" Wall      | 14, 17, 22, V22 (14" OAL w/ chk)     |
| 10108 | Plunger, 3/8-16 Thread  | X34 - blue head, R34              | 35725 | Rod Assy. 14" Wall      | 14, 17, 22, V22 (16" OAL w/ chk)     |
| 10109 | Yoke Nut                | Y30, Y70, Y95                     | 50009 | Tee Key, Short - 1 3/4" | 5/16" Square Stem                    |
| 10206 | Hex Nut                 | Y34, Y1, W34, X34                 | 50010 | Tee Key, Long - 3 1/4"  | 5/16" Square Stem                    |
| 10630 | Metal Oval Whl. Hdl.    | RHMC, Y30                         | 50012 | Tee Key, Long - 3 1/4"  | 8 Pt. Spline-14, 16, 17, 19, 22, V22 |
| 10633 | Metal Oval Whl. Hdl.    | Wheel Handle Utility Hydrants     | 50023 | Wheel Handle            | Y30                                  |
| 15001 | Head Assembly Page 23   | Y1                                | 50024 | Packing                 | All WH, Y70, Y95, Y30                |
| 15002 | Head & Nozzle           | Y1                                | 50027 | Washer                  | 32, 70                               |
| 15003 | Head Assembly Page 23   | Y34                               | 50028 | Nut                     | 32, 70                               |
| 15004 | Head & Nozzle           | Y34                               | 50040 | Door Hinge Pin          | All Wall Hydrant Boxes               |
| 15007 | Link, Lower             | Y34, Y1                           | 50250 | Plunger                 | All Auto Drain Hydrants              |
| 15008 | Cam & Clevis Assy       | Y34, Y1                           | 50251 | "C" Washer              | All Auto Drain Hydrants              |
| 15009 | Clevis & Set Screw      | Y34, Y1                           | 50252 | Stem Washer             | All Auto Drain Hydrants              |
| 15021 | Head & Nozzle           | X34                               | 50264 | Head Nut, Chrome        | All Auto Drain Hydrants              |
| 15037 | Head Assembly           | X34                               | 50502 | Gasket (2 Req)          | HC Series                            |
| 15039 | Head Assy., Complete    | W34                               | 51013 | Valve Rubber            | 70, 72                               |
| 15040 | Head & Nozzle           | W34                               | 51014 | Yoke Nut                | All Freezeless WH                    |
| 15050 | Pivot Assembly          | W34, X34                          | 51117 | Door Lock Screw Ch      | All Wall Hydrant Boxes               |
| 15220 | Diverter                | S3, S4H                           | 51120 | Door Lock Screw E-Ring  | All Wall Hydrant Boxes               |
| 15238 | Diverter                | Y2                                | 55062 | Stem Screw              | All Auto Drain Hydrants              |
| 15246 | Head & Nozzle           | R34                               | 55079 | Shuttle Housing Assy.   | HC Series                            |
| 15247 | Head Assembly           | R34                               | 55105 | Yoke Nut Assembly       | All Non-Freeze Area WH               |
| 30002 | Handle Screw, Br.       | 14, 17, 24/26 Series Y30          | 55176 | Head Nut Assy., Br      | All WH, Y70, Y95                     |
| 30006 | Packing Washer          | 14, 22, V22                       | 55177 | Head Nut Assy., Ch      | All WH, Y70, Y95                     |
| 30008 | Valve Rubber            | 14, 17, 19, 22, V22, 24/26 Series | 55178 | Head Nut Assy., Br      | Y30                                  |
| 30009 | Screw                   | 14, 17, 19, 22, V22, 24/26 Series | 55182 | Head Nut Assy., Br      | 75, B75, 79, B79                     |
| 30059 | Nut, Br                 | 14, 17                            | 55183 | Head Nut Assy., Ch      | 75, B75, 79, B79                     |
| 30096 | Wheel Handle-metal      | 14, 17                            | 55404 | Operating Rod Assy.     | Auto. Drain (6 5/16 OAL)             |
| 30104 | Stem                    | 24/26 Series                      | 55406 | Operating Rod Assy.     | Auto. Drain (8 5/16 OAL)             |
| 30105 | Washer                  | 24/26 Series                      | 55408 | Operating Rod Assy.     | Auto. Drain (10 5/16 OAL)            |
| 30107 | Packing Nut, Brass      | 24/26, WH, Y30 Series             | 55410 | Operating Rod Assy.     | Auto. Drain (12 5/16 OAL)            |
| 30109 | Packing Nut, Chrome     | 24/26, WH Series                  | 55412 | Operating Rod Assy.     | Auto. Drain (14 5/16 OAL)            |
| 30120 | Wheel Handle, Clear     | 24/26 Series                      | 55434 | Hose Nozzle Br          | 20, 22, V22, 60                      |
| 30121 | Screw, Nickel           | 24/26 Series, HC67, Y30           | 55435 | Nozzle W/o-ring, Brass  | 21, 70, Y70                          |
| 30230 | Plunger Assembly        | 20, 25, 27                        | 55437 | Nozzle W/o-ring, Ch.    | 70, 71, B71, 81                      |
| 30233 | Wheel Handle, Tan       | 24/26 Series                      | 80005 | Packing Nut             | Thermaline                           |
| 30234 | Handle Screw            | 20, 25, 27                        | 80008 | Packing Ring            | Thermaline                           |
| 30236 | Drain Guard             | 20, 25, 27                        | 80013 | Handle, Brass           | Thermaline                           |
| 30238 | Stem Screw              | 20, 25, 27                        | 80055 | Cover, Woodford         | Thermaline                           |
| 30239 | Wheel Handle, Metal     | 20, 25, 27                        | 80056 | Cover, Thermaline       | Thermaline                           |
| 30241 | Head Nut, Br            | 20, 25, 27                        | 80061 | Heater Cover            | Thermaline                           |
| 30245 | Head Nut Gasket         | 25                                | 80062 | Heater. Well Thumb Nut  | Thermaline                           |
| 30247 | Packing                 | 24/26 Series, B24                 | 80063 | Heater Well Washer      | Thermaline                           |
| 30304 | Operating Rod 4"        | 20, 25, 27                        | 80066 | Yoke Nut                | Thermaline                           |
| 30306 | Operating Rod 6"        | 20, 25, 27                        | 80068 | Wing Nut                | Thermaline                           |
| 30308 | Operating Rod 8"        | 20, 25, 27                        | 80073 | Carriage Bolt           | Thermaline                           |
| 30310 | Operating Rod 10"       | 20, 25, 27                        | 85001 | Heater Well Assy., 1'   | Thermaline                           |
| 30312 | Operating Rod 12"       | 20, 25, 27                        | 85002 | Heater Well Assy., 2'   | Thermaline                           |
| 30421 | Packing Washer          | 17                                | 85015 | Valve Assembly          | Thermaline                           |
| 30462 | C - Plug Button-small   | 22, V22                           | 85061 | Heater, 1'              | Thermaline                           |
| 30463 | H - Plug Button-small   | 22, V22                           | 85062 | Heater, 2'              | Thermaline                           |



# TERMS AND CONDITIONS OF SALE

**Selling Policy** - Possession of our price list or jobber discounts is not an offer to sell. All orders are subject to acceptance by the home office in Colorado Springs, Colorado.

**Minimum Invoice** - No invoice will be rendered for less than \$25.00 list.

**Cash Discount** - 3% 15 days from date of invoice or 2% 10th Prox., Net EOM

**Freight Allowance** - All goods sold F.O.B shipping point. For shipments in the continental United States and Canada, full freight will be allowed on orders of \$3,500.00 or more list. No freight allowance on smaller shipments. We reserve the right to ship the most economical way. Non-Standard lengths might not qualify for FFA.

**Foreign Shipments** - (including Alaska and Hawaii) will be allowed full freight, according to the conditions listed above, to the embarkation point in the continental United States only.

**Claims, Shortages and Damage** - All claims for shortages or goods damaged in transit must be made within **10 days after receipt of merchandise**. All claims must be made to **Woodford Manufacturing Co. by the consignee**.

**Prices, Designs and Quotation** - Prices, designs and dimensions of products are subject to change without notice. Quotations, unless otherwise stated, are for immediate acceptance and prices quoted are based on the sellers standard tolerances of materials. We reserve the right to invoice all merchandise at prices in effect at the time of shipment.

**Cancellations** - Orders covering special merchandise are not subject to cancellation without our written permission. Purchaser subject to expense incurred by cancellation of special orders.

**Limited Warranty** - All goods are sold with a limited warranty for one year against defects in material and workmanship. We will replace or issue credit (at our option) for defective goods that are returned for inspection and found to be defective within one year of purchase from Woodford.

**Implied warranties** - Implied warranties are limited to one year from date of purchase from Woodford.

**Taxes and Government Regulations** - Sales or manufactures tax imposed under any existing or future statutes shall be added to the price of merchandise effective at the time shipment is made.

**Ordering Procedure** - Purchase order must include the following: Model number, inlet size & type, handle type, wall thickness or depth of bury and type of finish required where applicable.

**Returned Goods** - Standard catalog material may be returned. All returns of resalable new and unused product is subject to a 25% restocking charge, plus the cost of reconditioning, not to exceed an additional 25% (50% total). Credit for used or freight damaged material to be determined by factory upon receipt of material. Polished Brass Finishes PB are subject to 50% restocking charge.

*We will not accept returns for:*

1. Any non-defective return under \$25.00 net or product over 18 months old.
2. Special lengths on any product.
3. Obsolete merchandise and product not listed in current price guide.
4. Competitor's product or product abused by installation
5. Items not reviewed and RGA form signed by local Woodford representative before being sent back for factory approval.

All items claimed defective must be returned prepaid to address shown on back cover:

## Model 19 Limited 5 Year Warranty



All Model 19 Wall faucets are sold with a limited warranty for five (5) years against defects in material and workmanship. We will replace or issue credit (at our option) for defective goods that are returned for inspection and found to be defective within five (5) years of purchase from Woodford. In addition, Woodford will pay up to \$5,000.00

toward the cost to repair damages incurred as a result of a defective Model 19 Wall Faucet that was properly installed. This limited warranty does not cover defects caused by: modification, alteration or repair of the product by anyone other than Woodford; physical abuse to, or misuse of, the product or operation thereof in a manner contrary to accompanying instructions.

## Commercial Limited 5 Year Warranty



All Commercial Wall hydrants and Roof hydrants shown in this brochure are sold with a limited warranty for five years against defects in material and workmanship. We will replace or issue credit (at our option) for defective goods that are returned for inspection and found to be defective within five years of purchase from Woodford.

Patented and Patents Pending: See [woodfordmfg.com](http://woodfordmfg.com) for details  
For Individual Spec Sheets, Installation and Troubleshooting Instructions  
Go to [woodfordmfg.com](http://woodfordmfg.com) or Call Customer Service 1-800-621-6032

To locate a Woodford Representative  
in your area please contact  
our sales department  
Toll Free (800) 621-6032



**WOODFORD MANUFACTURING COMPANY, LLC**

2121 Waynoka Road  
Colorado Springs, CO 80915 USA  
Phone (719) 574-1101  
Toll Free (800) 621-6032  
[www.woodfordmfg.com](http://www.woodfordmfg.com)