For Commercial Applications

Job Name	Item Designation
Job Location	Contractor
Engineer	Representative
nlet: P _ C _ (EP _ MADE TO ORDER, NO RETURN	RW) Finish: CH BR PB

For Non Freezing Areas

Woodford Model 84

Anti-Siphon Protected Close Coupled Wall Hydrant

The Model 84 is an Anti-Siphon Vacuum Breaker protected wall hydrant designed for use in mild climate areas or within temperature controlled malls and plazas.

Features:

- Red Brass head & valve body
- No lead solder All joints
- · Hemispherical valve seat
- Hardened stainless steel operating stem
- EPDM Packing
- · Adjustable brass packing nut
- · Loose Tee Key operation
- 3 Inlet options

Specifications:

- HOSE CONNECTION VACUUM BREAKER:
 - \bullet NIDEL® Model 34HF with $3\!\!/_4$ " hose connection
 - ASSE Standard 1011 approved
 - IAPMO® listed
 - Canadian Standards Association listed
 - Single check valve
- Maximum Working Pressure: 125 p.s.i.
- Maximum Temperature: 120° F

Specify as follows:


Wall hydrant shall be a Woodford Model 84 for non-freezing areas with anti-siphon vacuum breaker. ASSE Standard 1011 approved. 3/4" hose connection inlet. 3/4" outlet (specify type of inlet). Hardened stainless steel operating stem. Packing nut secured with lock nut. Permanent type valve body with large hemispherical seating surface. Exterior finish to be Chrome Plated (options: Rough Brass or Polished Brass). Loose tee key to be furnished with each hydrant.



Exterior Finish:

Standard - Chrome (CH)
Optional - Rough Brass (BR) or Polished Brass (PB)

Rough-In Dimensions



Inlet Options

P - 3/4" Female Pipe Thread C - 3/4" Copper Sweat Fitting EP - Union Elbow with 3/4" Male Pipe Thread



WOODFORD MANUFACTURING COMPANY, LLC

2121 WAYNOKA ROAD COLORADO SPRINGS, CO 80915 Phone (800) 621-6032 Website: www.woodfordmfg.com

Website: www.woodfordmfg.com Email: sales@woodfordmfg.com